

Stabilizer 434C™

Surfactant

Stabilizer 434C™ surfactant for latex cements is used to stabilize Latex 2000 cement. Latex 2000 cement is a water-internal, oil-external emulsion; in the presence of water, the system tends to come out of emulsion, losing its effectiveness against gas migration. Stabilizer 434C surfactant helps prevent the de-emulsification of Latex 2000 cement.

Features

Stabilizer 434C surfactant is a pale-yellow liquid additive that can be applied at temperatures from 80° to 380°F (27° to 160°C). The surfactant was developed specifically for use as a stabilizer for Latex 2000 cement.

Benefits

Stabilizer 434C surfactant has the following benefits:

- It stabilizes latex cement to keep it in emulsion.
- It is applicable over a wide temperature range.

Stabilizer 434C™ Surfactant—Product Specifications

Part No.	100064081	Boiling Point	212°F (100°C)
Form	Pale yellow liquid	Freeze Point	30°F (-1°C)
Specific Gravity	1.07	Flash Point	>200°F (>93°C)
Bulk Density	8.91 lb/gal	Packaging	45-gal drum
pH	7.3 to 7.8		

For more information on the benefits Stabilizer 434C™ Surfactant can bring to your cementing operations, contact your local Halliburton representative.

www.halliburton.com

H01341 08/07
© 2007 Halliburton
All Rights Reserved
Printed in U.S.A.

Sales of Halliburton products and services will be in accord solely with the terms and conditions contained in the contract between Halliburton and the customer that is applicable to the sale.

HALLIBURTON