

OMC®

THINNER

Product Description

OMC® thinner is used to reduce rheology in oil-based drilling fluids that have been treated with organophilic compounds such as GELTONE® viscosifiers or DURATONE® filtration control additive. OMC thinner can effectively reduce the yield point and gel strengths in these fluids. OMC thinner is suitable for INVERMUL® diesel-based drilling fluids and ENVIROMUL™ drilling fluids but should not be used in high performance clay-free drilling fluids.

Applications/Functions

OMC thinner can be used to reduce the yield point and gel strengths of oil-based drilling fluids

Advantages

- » Effective in small concentrations
- » Can be added directly to the system

Typical Properties

- » Appearance: Black liquid
- » Specific Gravity: 0.976

Recommended Treatment

Add 0.25-1.50 lb/bbl (0.71-4.28 kg/m³) of OMC thinner directly to the system.

Packaging

OMC thinner is packaged in 15-gal (56.8-l) pails, 55-gal (208-l) drums and in bulk.

OMC, GELTONE, DURATONE and INVERMUL are registered trademarks of Halliburton. ENVIROMUL is a trademark of Halliburton © 2017 Halliburton. All rights reserved. Because the conditions of use of this product are beyond the seller's control, the product is sold without warranty either express or implied and upon condition that purchaser make its own test to determine the suitability for purchaser's application. Purchaser assumes all risk of use and handling of this product. This product will be replaced if defective in manufacture or packaging or if damaged. Except for such replacement, seller is not liable for any damages caused by this product or its use. The statements and recommendations made herein are believed to be accurate. No guarantee of their accuracy is made, however.