

OMC® 2™

THINNER

Product Description

OMC® 2™ thinner is used to lower the rheological properties of oil-based drilling fluids that contain organophilic compounds or large amounts of drill solids. OMC 2 thinner works effectively in most oil-based drilling fluids and particularly well in the PETROFREE® fluid system. OMC 2 thinner should not be used in high performance clay-free drilling fluids. It is a powerful thinner; overtreatment can cause a severe reduction of low shear rheology. OMC 2 thinner is environmentally more responsible than OMC thinner.

Applications/Functions

OMC 2 thinner can be used to reduce the yield point and gel strengths of oil-based drilling fluids

Advantages

- » Effective in small concentrations
- » Can be added directly to the system

Typical Properties

- » Appearance: Viscous amber liquid
- » Specific Gravity: 0.89

Recommended Treatment

Add 0.1-0.5 lb/bbl (0.29-1.43 kg/m³) of OMC 2 thinner directly to the system.

Packaging

OMC 2 thinner is packaged in 5-gal (18.9-l) pails, 40-gal (152-l), and 55-gal (208-l) drums.

OMC and PETROFREE are registered trademarks of Halliburton. OMC 2 is a trademark of Halliburton © 2017 Halliburton. All rights reserved. Because the conditions of use of this product are beyond the seller's control, the product is sold without warranty either express or implied and upon condition that purchaser make its own test to determine the suitability for purchaser's application. Purchaser assumes all risk of use and handling of this product. This product will be replaced if defective in manufacture or packaging or if damaged. Except for such replacement, seller is not liable for any damages caused by this product or its use. The statements and recommendations made herein are believed to be accurate. No guarantee of their accuracy is made, however.