

OMC® 42™

THINNER

Product Description

OMC® 42™ thinner is used to reduce the rheological properties of all oil-based drilling fluids that contain large amounts of drill solids. It is suitable for use in ACCOLADE®, ENCORE® and INNOVERT® high performance oil-based drilling fluids and does not affect the emulsion chemistry of these fluids.

Applications/Functions

OMC 42 thinner can be used to reduce the yield point and gel strengths of non-aqueous drilling fluid systems

Advantages

- » Effective in small concentrations
- » Can be added directly to the system

Typical Properties

- » Appearance: Brown liquid
- » Specific Gravity: 0.92

Recommended Treatment

Add 0.25-1.50 lb/bbl (0.71-4.28 kg/m³) of OMC 42 thinner directly to the system.

Packaging

OMC 42 thinner is packaged in 15-gal (56.8-l) pails, 55-gal (208-l) drums and in bulk.

OMC, ACCOLADE, ENCORE and INNOVERT are registered trademarks of Halliburton. OMC 42 is a trademark of Halliburton © 2017 Halliburton. All rights reserved. Because the conditions of use of this product are beyond the seller's control, the product is sold without warranty either express or implied and upon condition that purchaser make its own test to determine the suitability for purchaser's application. Purchaser assumes all risk of use and handling of this product. This product will be replaced if defective in manufacture or packaging or if damaged. Except for such replacement, seller is not liable for any damages caused by this product or its use. The statements and recommendations made herein are believed to be accurate. No guarantee of their accuracy is made, however.